

AZH500

Eco-friendly compact high brightness Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -5200 lumens and IP6X certified
- Compact for easy installation 1.3x zoom, 360degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The AZH500 is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, it delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.¹

An added benefit, the AZH500 features an external power supply offering more reliability, portability and energy efficiency.

Specifications

Display/image DIPTM Display technology

Resolution 1080p Full HD (1920x1080)

Brightness 5,200 lumens Contrast ratio 300,000:1 Contrast ratio - dynamic 3,000,000:1 Native aspect ratio 16.9 Aspect ratio - compatible 4:3,16:9,16:10

Keystone correction -30°

horizontal Keystone correction - vertical 30° Displayable colours (millions) 1073.4 75% Uniformity

Lamp info Light source type 30,000 hours LASER life Optical Throw ratio 1.13:1 ~ 1.47:1 Projection distance 1m - 8m Zoom 1.3 Zoom type Manual Focal length 16.90 ~ 21.61

116%

Native offset Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232, 1 x RJ45

General Noise level (min) 29dB 31dB Noise level (max)

PC compatibility UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-r

3D compatibility Full 3D

3D

Security Security bar, Kensington Lock, Password protected interface

IP rating

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Tinnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

Operating conditions 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

Remote control Card style Speaker count Watts per speaker 15W In the box AC power cord Remote control

1x CR2025 battery Basic user manual

Power

Power supply External power supply, 100V ~ 240V, 50-60Hz

Power consumption (standby) <0.5W Power consumption (min) 160W 258.75W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) 274 x 216 x 114 Gross weight 4.5 kg Net weight 2.9 kg



