

HD36UST

Bright and Feature-Oriented Companion

- Vertical auto keystone
- Four corner adjustment
- Built-in USB reader
- USB display
- WiFi & LAN display



Specification

Display Technology	Texas Instruments DLP® technology/ 0.65" 1080p DMD Chip	Native Resolution	Native: 1920x1080 1080p Support Computer signal up to UXGA, 1600 x1200, 60Hz WUXGA for WXGA (16:10)
Brightness / Contrast Ratio	4000lm / 22,000:1	Display Colors	1073.4 million colors (10bit)
Projection Lens	F=2.4 ; f = -3.72 mm; fixed zoom	Image Size	80~100 inch
Projection Distance	0.446m~0.558m	Throw Ratio (Projection distance/width)	0.25
Digital Keystone Correction	±4° Vertical ±4° Horizontal	Aspect Ratio	16:9 Native, 4:3 Compatible
Lamp Type	240W	Noise	25 dB (Eco mode)
Video Compatibility	HDTV (720p, 1080i/p), SDTV (480i/p, 576i/p)	Lamp Life	4000 / 10000 / 15000 Hrs (Bright/Eco/Dynamic)
Uniformity	80 %	Speaker	16W speaker
Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac	Input / Output Connections	HDMI v1.4a x 1 , HDMI/MHL x 1 , VGA-in x1, VGA-out x1, Composite x1, Audio-in x1, Audio out x 1 , USB-A x1(USB Display/USB Reader), USB-A x1(Wifi), RS232x1, RJ45x1
Scan Rate	Horizontal : 15.375 ~ 91.146 KHz ; Vertical :24 ~ 85 Hz (120Hz for 3D feature)		
Dimensions(W x D x H)/ Weight	343 x 383 x 96.5mm (WxDxH) (w/o feet) / 3.9kg	Power Supply	Universal AC 100 ~ 240V± 10%,50/60Hz