

Telescopic boom 930-1530mm (centre-of-projector to wall)
Projector can be mounted at any point along boom
Adjustable boom incline



The Techmount ST2 supports 99% of short-throw and ultra-short-throw projectors with no extra parts required. It is a strong, flexible mount which uses Vision's universal spider fitting to attach projectors.

Long Boom

The boom is up to 1530mm – long enough for short throw projectors to project an image 2000mm wide. The spider can be mounted at any point along the boom.

Telescopic

The two-part boom allows easy adjustment of image size. Cables are dropped down the pole during assembly. The pole which fits to the wall bracket is 800mm (31.5") long, and the outer pole is 900mm (35.4") long.

Gradient Adjustment

A flexible wall plate allows the installer to alter the slope of the boom to offset the weight of heavy projectors.

Projector Tilt

The TM-ST2 allows plenty of roll adjustment.

Fine Adjustment

The wall plate gives the installer some fine-tuning adjustment of the boom up and down and side to side.

Security Bit

The TM-ST2 uses pin-hex security bolts which require a bespoke hex key. Vision includes a pin-hex drill bit to help assemble the product quickly using a power drill.

One-Person Installation

The modular design makes it simple to fit quickly. Just fix the wall mount in place, fit the boom, then attach the projector.

SPECIFICATIONS

BOOM LENGTH

930-1530mm

WALLPLATE FOOTPRINT

250 x 152 mm (height x width)

BOX DIMENSIONS

1160 x 160 x 115 mm

PACKAGED WEIGHT

6 kg

SAFE WORKING LOAD

10kg

COLOUR

Satin White

ACCESSORIES INCLUDED

1 x H50 Pin-Hex key 1 x 17mm Spanner 4 x M2.5 40mm pan slot for Optoma & Acer 4 x M3 40mm screws 4 x M4 40mm screws 4 x M5 40mm screws 4 x M6 40mm screws 4 x M8 50mm Wall Fixtures 1 x Wall Plate Cover 1 x Boom End Cap 1 x Safety Fall-Arrest Tether

WARRANTY

Lifetime return-to-base

COMPLIANCES

RoHS, TUV-GS

