



Avision AN360W A4 Document Scanners AV5385



The Avision AN360W is a 60 page-per-minute (120 ipm) duplex network document scanner. A true stand-alone network scanner, i.e. it doesn't require any software to be installed on the workstations or on a server. The AN360W scans a wide range of documents, delivery docket, invoices, plastic ID cards, business cards or other heavy card stock. Documents can be sent in a variety of formats including PDF and text searchable PDF. Destinations include: local network folders, e-mail (including via Exchange mail server), cloud servers (such as Google Drive, Dropbox, Evernote), SharePoint Server, FTP server, USB flash drive or the scanner's memory. The Avision AN360W is also Wi-Fi enabled. The large 8" LCD touch screen makes it easy to scan and access frequently used destinations via your own shortcuts.

Avision AN360W

A4 Document Scanners

| AN360W Specifications | |
|------------------------------|--|
| ADF (Doc. Feeder) | Yes |
| ADF Scan Area - Max. | 216x356 mm (up to 6m long with limitations) |
| ADF Scan Area - Min. | 50x50 mm |
| Duplex or Simplex | True Duplex |
| ADF Speed (ppm) | 60 |
| ADF Capacity (pages) | 100 |
| ADF Speed Duplex (ipm) | 120 |
| Flatbed | N/A |
| ADF Paper Path | Straight |
| Paper Weight | 27 - 413 g/m |
| Duty Cycle | ★★★★★ |
| Colour Modes | B&W, Greyscale, Colour |
| Scanning Technology | CIS |
| Interface | USB3.1 Gen 1, Gigabit Ethernet, Wi-Fi |
| Resolution (dpi, optical) | 600 |
| File Formats | BMP, PNG, GIF, JPEG, Single page PDF, Multi-page PDF, Multi-TIFF, TIFF, RTF, TXT, OCR (for iScan only), XPS, DOC, XLS, PPT, DOCS, XLSX, PPTX, HTML |
| Supported OS | OS independent in network scanner mode - Win Win7 / Win8 / Win10 (32 & 64 bit) in Twain mode |
| Software Standards | TWAIN |
| Imaging Features | Auto crop, Deskew, Searchable PDFs, Send images to cloud servers including Google drive, Dropbox, Evernote). |
| In the Box | Power supply, Quick guide, USB cable, CDROM (TWAIN Driver, Button Manager v2, AVSCAN X, Nuance PaperPort SE) |
| Electrical | Input: 100-240 VAC, 50/60 Hz. Power consumption: |
| Light Source | LED x2 |
| Dimensions | 316x207x178 mm |
| Weight | 6 |
| Operating Environment | 10°C to 35°C, 10-85%RH |
| Warranty | 12 months parts & labour warranty |