

Avision AV5200 A3 Document Scanners AV3090



The AV5200 Document Scanner is an A3 document scanner capable of scanning up to A3 sized documents at a scanning rate of 30 pages per minute in simplex mode and 60 images per minute in duplex mode. The AV5200 with CIS technology is suited to scan complete book spreads, two letter-sized pages simultaneously, photographs and any other large sized documents you can think of in brilliant colour. If large amounts of paper need to be scanned, the optional auto-document feeder allows the user to scan 50 page documents continually at any time. The scanner has the convenient feature of multiple images cropping. Various sized documents such as photos, ID Cards, or business cards can be placed on the flatbed and the scanner is able to crop and create multiple images according to the original sizes of the documents in one single scan. The Avision AV5200 has a USB 2.0 interface.

Main features: 30ppm (60ipm), FB+50p ADF, A3, True Duplex, USB2, for Windows (Mac optional), 1 year warranty RTB.

Avision AV5200 A3 Document Scanners

AV5200 Specifications	
ADF (Doc. Feeder)	Yes
ADF Scan Area - Max.	297x910 mm
ADF Scan Area - Min.	148x210 mm
Duplex or Simplex	True Duplex
ADF Speed (ppm)	30
ADF Capacity (pages)	50
ADF Speed Duplex (ipm)	60
Flatbed	Yes
ADF Paper Path	U
Flatbed Scan Area	A3 (297x420 mm)
Paper Weight	60 to 105 gsm
Duty Cycle	常能物化
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CIS
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, TIFF, JPEG, GIF, BMP
Supported OS	WINDOWS XP, VISTA, Win 7, Win 8 (MAC OS X optional)
Software Standards	TWAIN, ISIS drivers
Imaging Features	Deskewing, sharpening, auto-crop, blank page removal, page separation, dynamic thresholding, noise removal
In the Box	Button Manager, AVScan, Paperport SE, USB cable
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption: 30W
Light Source	LED
Dimensions	585x499x195 mm
PC Configuration	Minimum: 1GB RAM, USB2. Recommended: 4GB RAM, USB2
Weight	16.5
Operating Environment	10°C to 35°C, 10-85%RH
Warranty	12 months parts & labour warranty



