

Avision FB2280E Bookedge A4 Flatbed Scanners



The Avision FB2280E Bookedge scanner is a flatbed scanner with Bookedge scanning. A4, USB2. Ideal for books, magazines, office documents, photos. Scan within 2mm of a book's spine without shadows or curvature. The Avision FB2280E is optimised for super fast scanning of office documents, books and magazines. It's capable of scanning within 2mm of the a book's spine without the shadows, distortion & page skewing encountered with conventional scanners. The Bookedge design is also easier on the books and thanks to its exceptional speed and image quality, the FB2280E is also a great way to scan artwork, drawings or office documents. In addition, the FB2280E scanner comes with the convenient feature of multiple image cropping. With this feature, various sizes of documents such as photos, ID Cards, or business cards can be placed on the flatbed and the scanner is able to crop and output separate images for each original document in one single scan. The FB2280E can be daisy chained with most other Avision ADF scanners (e.g. an AV176U, AV188, AV280) and be treated as one scanner by the scanning software. No need to switch from one scanner to the other.

Main features: Flatbed scanner with Bookedge scanning. A4, USB2. Ideal for books, magazines, office documents, photos. Scan within 2mm of a book's spine without shadows or curvature. 4 second A4 colour scan, for Windows (Mac optional), 1 year warranty RTB.

Avision FB2280E Bookedge A4 Flatbed Scanners

FB2280E Bookedge Specifications	
Flatbed	Yes
Flatbed Scan Area	A4+ (216x297 mm)
Duty Cycle	京政治市
Colour Modes	B&W, Greyscale, Colour
Scanning Technology	CCD
Interface	USB2
Resolution (dpi, optical)	600
File Formats	Text Searchable PDF, TIFF, JPEG, GIF, BMP
Supported OS	WINDOWS XP, VISTA, Win 7, Win 8 (MAC OS X optional)
Software Standards	TWAIN, ISIS drivers included
Imaging Features	Deskewing, sharpening, auto-crop, blank page removal, page separation, dynamic thresholding, noise removal
In the Box	Button Manager, AVScan, Paperport SE, USB cable
Electrical	Input: 100-240 VAC, 50/60 Hz. Power consumption: 30W
Light Source	LED
Dimensions	288x480x115 mm
PC Configuration	Minimum: 1GB RAM, USB1. Recommended: 2GB RAM, USB2
Weight	7
Operating Environment	10°C to 35°C, 10-85%RH
Warranty	12 months parts & labour warranty



