

MITSUMARU

Smart Digital Signage

32MDI25FSD
43MDI25FSD
49MDI25USD
55MDI25USD
65MDI25USD
75MDI25USD
86MDI25USD

ULTRA HIGH BRIGHTNESS DIGITAL SIGNAGE DISPLAYS

32" / 43" / 49" / 55" / 65" / 75" / 86"



Ultra Slimline Bezels



Landscape/Portrait Orientation



2500nit Brightness Levels



24/7 Rated Displays



Android OS



3 Year Commercial Warranty

Stand out from the rest...!! Mitsumaru's spectacular ultra high bright signage displays offer unsurpassed, stunning picture quality courtesy of the 2500nit brightness levels, coupled with FHD & UHD (4K) resolutions. Your content will be deployed in breathtaking clarity. With an unmatched range of sizes to choose from, Mitsumaru's ultra high brightness displays will ensure your signage project stands head and shoulders above all others.

Powered by Android OS and with Wi-Fi network connectivity, installation of native and customised Apps is a breeze. For an indoor signage solution requiring the absolute pinnacle in image and picture quality, look no further than Mitsumaru's ultra high brightness signage range.

fusion signage

Content is King...!! Mitsumaru's Smart Digital Signage range is complemented by Fusion Signage, Australasia's premier Content Management System. Let the Mitsumaru / Fusion partnership deliver your turn key digital signage solution.

Visit Mitsumaru & Fusion at:
www.mitsumaru.com.au
www.fusionsignage.com.au

MITSUMARU

Smart Digital Signage

32MDI25FSD
43MDI25FSD
49MDI25USD
55MDI25USD
65MDI25USD
75MDI25USD
86MDI25USD

Panel

Size	32"	43"	49"	55"	65"	75"	86" TBC
Active Display Area	698 x 392	941 x 529	1073 x 604	1210 x 680	1428 x 803	1650 x 928	
Resolution	1920 x 1080	1920 x 1080	3840 x 2160	3840 x 2160	3840 x 2160	3840 x 2160	
Aspect Ratio	16 : 9	16 : 9	16 : 9	16 : 9	16 : 9	16 : 9	
Brightness	2500 nits	2500 nits	2500 nits	2500 nits	2500 nits	2500 nits	
Viewing Angle	178 / 178°	178° / 178°	178° / 178°	178° / 178°	178° / 178°	178° / 178°	
Backlight Configuration	LED	LED	LED	LED	LED	LED	
Operation Life Cycle-mtbf(hours)	50,000	50,000	50,000	50,000	50,000	50,000	
Bezel Dimensions(mm)	8.5 (T/L/R/B)	8.5 (T/L/R/B)	8.5 (T/L/R/B)	8.5 (T/L/R/B)	8.5 (T/L/R/B)	8.5 (T/L/R/B)	

Environmental

Operating Environment	Indoor
Operating Temperature	0° C ~ +40° C
Operating Humidity	10% ~ 80%
Operating Altitude (m)	≤ 2000

Mechanical

Dimensions (W x H x D) mm	722 x 417 x 58	963 x 551 x 58	1231 x 702 x 58	1231 x 702 x 58	1450 x 825 x 58	1680 x 959 x 64
Nett Weight (KG)	8.60	14.50	17.80	20.50	29.20	39
Enclosure	Light Weight Steel	Light Weight Steel	Light Weight Steel	Light Weight Steel	Light Weight Steel	Light Weight Steel
Finishing	Fine Grain Powder Coating	Fine Grain Powder Coating	Fine Grain Powder Coating	Fine Grain Powder Coating	Fine Grain Powder Coating	Fine Grain Powder Coating
Colour	Black (RAL 9005)	Black (RAL 9005)	Black (RAL 9005)	Black (RAL 9005)	Black (RAL 9005)	Black (RAL 9005)

Power

AC Input	100 VAC / 240 VAC, 50 / 60 Hz					
Power Consumption (w)	100	156	198	308	460	500

Media

OS	Android 9.0 (32" & 43") Android 7.1 (49", 55", 65", 75")
CPU	ARM Cortex A53 1.5GHz
GPU	ARM Mali- 450
Memory	1GB DDR3 (32" & 43") 2GB DDR4 (49", 55", 65", 75")
ROM	8GB (eMMC)
HDMI Input	x 1
USB Input	x 2
LAN	x 1
AV-IN	x 1
TF	x 1
SIM	x 1
Wi-Fi	802.11 b/g/n
RS-232	x 1

SMART DIGITAL SIGNAGE

All rights reserved. Equipment design and specifications may be changed without notice.

Visit Mitsumaru & Fusion at:
www.mitsumaru.com.au
www.fusionsignage.com.au